

两相混合式步进电机

S60D步进齿轮箱电机

□ 60mm



单极

Post Connector

参数

型号		保持转矩	转子惯量	额定电流	额定电压	卷线电阻	卷线电感	基本步进角	减速比	容许转矩	容许转速	重量
		HOLDING	ROTOR	RATED	RATED	WINDING	WINDING	SETPPING	GEAR	ALLOW OF	ALLOW OF	MASS
SINGLE SHAFT	DOUBLE SHAFT	TORQUE	INERTIA	CURRENT	VOLTAGE	RESISTANCE	INDUCTANCE	VOLTAGE	RATIO	TORQUE	SPEED	Kg
		(N.m)	(Kg.m ²)	(A/相)	(V)	(Ω/相)	(mH/相)	度		(N.m)	(r/min)	
S60D120A-MA3R6	S60D120B-MA3R6	1	135x10 ⁻⁷	2	2.2	1.1	1.1	0.5°	1:3.6	1	0~500	0.8
S60D120A-MA7R2	S60D120B-MA7R2	2	135x10 ⁻⁷	2	2.2	1.1	1.1	0.25°	1:7.2	2	0~250	0.8
S60D120A-MA009	S60D120B-MA009	2.5	135x10 ⁻⁷	2	2.2	1.1	1.1	0.2°	1:9	2.5	0~200	0.8
S60D120A-MA010	S60D120B-MA010	2.7	135x10 ⁻⁷	2	2.2	1.1	1.1	0.18°	1:10	2.7	0~180	0.8
S60D120A-MA018	S60D120B-MA018	3	135x10 ⁻⁷	2	2.2	1.1	1.1	0.1°	1:18	3	0~100	0.8
S60D120A-MA036	S60D120B-MA036	4	135x10 ⁻⁷	2	2.2	1.1	1.1	0.05°	1:36	4	0~50	0.8
S60D120A-MA050	S60D120B-MA050	4	135x10 ⁻⁷	2	2.2	1.1	1.1	0.036°	1:50	4	0~36	0.8
S60D120A-MA100	S60D120B-MA100	4	135x10 ⁻⁷	2	2.2	1.1	1.1	0.018°	1:100	4	0~18	0.8

外形尺寸 (例)

